### an**300**

#### **Features:**

- Main motion by servomotor.
- Independent temperature calibration of each sealing jaw from touch screen.
- HMI screen for multiple recipes.
- Total hermetic and monobloc machine.
- Easy access for sealing system cleaning (without death corners). Tool-free.
- Expansible reel shaft.
- Automatic photocell.
- End of reel detector.

### Filling System:

- Volumetric filler.
- Auger filler.
- Piston pumps.
- Flowmeter.
- Timing filler.
- Counting filler.



# Medium-scale production


Machine designed for **low productions** and market **testing purposes**. **From 1 to 4 lanes**.

\_Our equipment





Josep Tura 11-f, Polígon Industrial Mas d'en Cisa E-08181 Sentmenat, BARCELONA – Catalonia Tel: +34 937 154 676 Fax: +34 937 154 677





## **Stickpack**

an**300** 

Machine designed for **low productions** and market **testing purposes**. From 1 to 4 lanes.

**Downtimes reduction** due to **user friendly** and simple design, low maintenance and easy access.

# **Optimal** implementation & performance

Personalized **Customer Service** support with local technicians.

**Overall Equipment** Efficiency (OEE) > 95%


CONCEPT	DATA
Max. reel width	300 mm
Lanes number	1 - 4 lanes
Stickpack width range	14 - 80 mm
Max. stickpack length	160 mm*
Reel shaft	70 mm
ø Reel max.	450 mm
Max. production	300 spm
Standard power consumption	3 kw
Standard air consumption (I./min)	180 l.

<sup>\*</sup> Other dimensions under request.













1. Liquid.









