

an**650**^{TW}

Features:

- High production performance (OEE >95%).
- Full customer service along machine life.
- Main motion servomotorized.
- High filling accuracy controlled from HMI.
- Easy access for sealing system cleaning. Tool-free.
- Additional vertical sealing twinpack to combine two product types.
- Possibility of vertical pre-cut to separate both products.
- Possibility of twinpack-shaped stick
- Independent lane rejection (reject/sampling), fail safe mode.
- GMP Compliance.
- Independent temperature calibration of each sealing jaw from touch screen.
- Remote diagnosis via ethernet.
- Total hermetic and monobloc machine.
- Stickpack length automatically adjustable.
- CIP and/or SIP procedures.
- HMI for multiple recipes.
- Transfer systems to secondary packaging equipment.
- Empty stick detector.
- Programmable string option.
- Centralized lubrication.
- Unwinder with safety lock doors.
- Automatic reel alignment.
- Expansible reel shaft.

Additional features:

- Laser/Thermoprinter/Inkjet/Thermotransfer.
- Vacuum/auger/elevator feeding systems.
- Anti-static bar.
- UV lamp.

Stickpack type:

- Lap seal.
- Fin seal.
- Twinpack.

Filling system:

- Volumetric filler.
- Auger filler.
- Piston pumps.
- Flowmeter.

an**650**^{TW} **Twinpack**

Multilane machine designed for **twinpack format sticks**. Up to 8 lanes.

_Our equipment

aranow
packaging
machinery



Josep Tura 11-f, Poligon Industrial Mas d'en Cisa
E-08181 Sentmenat, BARCELONA – Catalonia
Tel: +34 937 154 676
Fax: +34 937 154 677
www.aranow.com



Catalonia
Packaging machinery manufacturers

aranow
packaging
machinery

Twinpack

an650^{TW}

The **an650-TW** has been specially created to offer high performance in the packaging process of **two different products into the same sachet**. Liquid + liquid, powder + powder or liquid + powder. From general food applications including hotel amenities up to pharmaceutical solutions.

Downtimes reduction
due to **user friendly and simple design**, low maintenance and easy access.

Optimal
implementation
& performance

Personalized Customer Service
support with local technicians.

Overall Equipment Efficiency (OEE) > 95%

CONCEPT

Max. reel width

Lanes number

Stickpack width range

Max. stickpack length

Reel shaft

Ø Reel max.

Max. production

Standard power consumption

Standard air consumption (l./min)

DATA

650 mm

2 - 5 lanes

60 - 80 mm

180 mm*

76 mm

450 mm

300 spm

5 kw

220 l.

* Other dimensions under request.



1. Double filler (powder - liquid).



2. Twinpack sealing system.



Powder, granulate, liquid, shaped stick pouch.